



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO 1532 AB Coated Fiberglass Fabric

Product Specifications

LEWCO Style 1532 AB is a lightweight, woven, asbestos free fiberglass fabric suitable for light sparks or spatters when used in welding, metal cutting, and grinding operations. This material should be oriented as a curtain or draped downward to allow hot metal to roll off. This material should not be used to catch and hold molten slag. LEWCO has available other fabrics to catch and hold molten slag. This fabric has a special coating to prevent fraying and fly. Lewco 1532AB has been tested and meets NFPA 701-1999 Fire Tests For Flame Retardant Textiles and Films Method 1. This fabric is made to conform to Mil-C-20079 Type 1 Class 2.

Typical Properties

Color	Black
Weight	14 Oz./Sq. Yd.
Thickness	.0145 Inches
Weave	Crowfoot
E Glass Melting Point	1523 ° F
Maximum Continuous Temperature	1100 ° F
Maximum Temp of Acrylic Coating	350 ° F
Width	60 Inches
Roll Length	50 Yards

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in working with welding curtains and fire blankets. All liabilities are borne by the user of this fabric. LEWCO does not take any responsibility for misuse of these products. LEWCO recommends testing before use.

S1532AB-01/09/12JDG