



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO Neoprene Coated Fiberglass Fabric

Product Specifications

LEWCO Styles 1600 N, 2400 N and 3000 N are asbestos free woven fiberglass fabrics coated on both sides with neoprene elastomers. This fabric was developed for welding curtains, blankets and screens to provide protection from molten metal splash. Standard stock color is Black: other colors available upon request. This fabric has been designed to prevent dust and fly. Lewco 1600 N has been tested and meets NFPA 701-1999 Fire Tests for Flame resistant Textiles and Films Method 1. Lewco 2400 N has been tested and meets NFPA 701-1999 Fire Tests for Flame resistant Textiles and Films Method 2.

Typical Properties

	<u>1600N</u>	<u>2400N</u>	<u>3000N</u>
Color	Various	Various	Various
Weight (Oz./Sq.Yd.)	16.0	24.0	30.0
Thickness	.016"	.045"	.052"
Width	40" & 60"	60"	60"
Weave	Satin	Plain	Plain
Maximum Temperature	Base Fabric 1100°F Coating 250°F		

For use in well ventilated areas only.

This information is given in good faith and is believed to be accurate. It is intended for use by persons experienced in working with welding curtains or fire blankets. LEWCO recommends testing before use.

S1600NS2400NS3000N-07/14/04MEDREV01.