



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO Plain Fiberglass Fabric

Product Specifications

Styles 2400 F, 3000 F, 3500 F, 4000 F and 6000 F are asbestos free woven as a high temperature heat resistant fabric. Some applications include fire blanket, removable Insulation jacketing, fire shielding, gasketing and many others. These products are manufactured from 100% E Grade Fiberglass and are developed to conform to US Coast Guard 164.009.

Typical Properties

	<u>2400 F</u>	<u>3000 F</u>	<u>3500 F</u>	<u>4000F</u>	<u>6000 F</u>
Color	White	White	White	White	White
Weight (Oz./Sq.Yd.)	24.0	30.0	35.0	40.0	60.0
Thickness	.065"	.070"	.080"	.090"	.125"
Construction	20 x 8	20 x 8	20 x 7	20 x 8	10 x 7
Weave	Plain	Plain	Plain	Plain	Plain
Breaking Strength	240 * 220	240* 220	240 * 450	250 * 475	450 * 420
Continuous Temp.	1100 ° F	1100 ° F	1100 ° F	1100 ° F	1100 ° F

***Available with reinforced stainless steel wire .0045 Inches**

This information is given in good faith and is believed to be accurate. All liabilities are borne by the user of this fabric. LEWCO does not take any responsibility for misuse of this product. LEWCO recommends testing before use.

S2400-6000F-5/2004MED