



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO 332-2L

Light/Medium Weight Fiberglass Fabric

Product Specifications

LEWCO 332-2L is a light weight, inexpensive, woven, nonflammable, asbestos free fiberglass fabric suitable for light sparks and spatter when used in welding, metal cutting, and grinding operations. This material should be oriented as a curtain or draped downward to allow hot metal to roll off. This material should not be used to catch and hold molten slag. LEWCO 332-2L has been tested and meets NFPA 701-1999 Fire Tests for Flame-Resistant Textiles and Films Method 1.

Typical Properties

Weight	13.75 Oz./Sq. Yd.
Thickness	.025 Inches
Weave	Satin
Construction	Warp – ECG 37 1/0 Fill - ECG 11.6T
Thread Count	48 x 14
Breaking Strength	500 * 400 W F
Maximum Temperature	1100 ° F
Melt Point	1523 ° F
Width	60 Inches
Roll Length	50 Yards

This information is given in good faith and is believed to be accurate. It is intended for use by persons experienced working with welding curtains or fire blankets. All liabilities are borne by the user of this fabric. LEWCO takes no responsibility for misuse of these products and recommends testing before use. S332-2L-05/18/04MED