



6859 Renoir Avenue  
Baton Rouge, LA 70806

Tel: (225) 924-3221  
Fax: (225) 927-2918

## **LEWCO 3600HTS**

### **Silicone Coated Silica Fabric**

#### **Product Specifications**

This material is a one-side or two-side silicone coated silica fabric. The silicone coating resists abrasion and weathering on the base silica fabric. LEWCO Style 3600 HTS has been specially designed for use on the weather barrier/cold face side only of removable-reusable thermal insulation jacketing in high temperature turbine or engine exhaust applications.

#### **Typical Properties**

Color	Various
Weight (Oz./Sq./Yd.)	36.0
Thickness	.050"
Weave	12-H Satin
Silica Content – Fabric	98%
Silicone Coating	3 Mils/Side
Breaking Strength	480 * 330 W F
Silicone Coating Max Temp	500 ° F
Steady Use Temp Fabric/without coating	1800 ° F
Melt Point (Fabric)	3000 ° F
Width	36"

---

This information is given in good faith and is believed to be accurate. LEWCO Specialty Products, Inc bears no responsibility for application of this product. It is intended for use by persons skilled in the art of fabricating and applying removable/reusable insulation or like products. All liabilities are borne by the user. Samples are available upon request for testing.

S3600HTS-06/09/04MED