



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO Braided Tubing

Typical Properties

<u>1/16" Wall Thickness</u>		<u>1/8" Wall Thickness</u>	
<u>Nominal I.D. – Approx. Ft./Spool</u>		<u>Nominal I.D.-Approx. Ft./Spool</u>	
1/8 " -	2525	1/4 " -	631
1/4 " -	1275	3/8 " -	363
3/8 " -	760	1/2 " -	269
1/2 " -	526	5/8 " -	250
5/8 " -	435	3/4 " -	159
3/4 " -	321	1" -	121
1" -	280	1 1/4" -	100
1 1/4 " -	240	1 1/2" -	89
1 1/2" -	226	1 3/4" -	85
1 3/4" -	215	2 " -	81
2" -	189	3 " -	54
3" -	104		

Continuous Temperature Resistance: 1100 ° F
Standard Spool Size: 25 Pounds
5 lb. Spools available upon request
This is also available in 100' lengths.

Silicone Coated Tubing

Available only in 1/8" Wall Thickness Nominal I.D. – 1/2", 3/4", 1", 1 1/2", 2", 3"
Maximum Temperature Resistance: 500° F Available in 25 foot lengths

This information is given in good faith and is believed to be accurate. All liabilities are borne by the user. LEWCO does not take any responsibility for misuse of these products. LEWCO recommends testing before prior to use. SBRTUBING-05/18/04MED