



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO VERMICULITE COATED FIBERGLASS TAPES

Product Specifications

LEWCO Vermiculite Coated Fiberglass Tapes are manufactured from continuous filament texturized fiberglass yarns. Woven into a strong and flexible tape with vermiculite coating which adds higher temperature resistance and adds to its ability to withstand direct flame, as well as increase the product's abrasion resistance. Our vermiculite coated fiberglass tapes provide a dust suppression coating which allows for a safer work environment.

Typical Properties

	<u>FT24 – Z</u>	<u>FT60 - Z</u>
Thickness	.060"	.125"
Weave	Plain	Plain
Continuous Temperature	1500 ° F	1500 ° F
Max Temp for Short Durations	2000 ° F	2000 ° F
Roll Length	100 Ft.	100 Ft.
Roll Widths:	1", 1 1/2", 2", 2 1/2", 3", 3 1/2", 4", 4 1/2", 5", 5 1/2", 6"	

This information is given in good faith and is believed to be accurate. LEWCO takes no responsibility for misuse of this product. All liabilities are borne by the user. LEWCO recommends testing before use.

SFTZTAPES-06/09/04MED