



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO 1650 T-BLK PTFE/Teflon Impregnated Fiberglass Fabric

Product Specifications

LEWCO Style 1650 T is an asbestos free woven fiberglass fabric impregnated with PTFE Teflon resins, then top coated with pigmented Teflon. This coating is impervious to most known chemicals, will not stain, and cleans easily. LEWCO Style 1650 T has a fairly stiff feel and has excellent abrasion, tear, and puncture resistance. This is a very durable medium weight fabric for removable insulation blankets.

Typical Properties

		<u>Test Method</u>
Color	Black	
Maximum Temperature (PTFE) (Melting)	550 ° F	
Minimum Temperature	-40 ° F	
Base Fabric Type & Weave	4 Harness Satin Fiberglass	
Weight	16.5 Oz./Sq. Yd.	ASTM D-3776-96
Thickness	.016 Inches	ASTM D-1777-96
Width	60 Inches	
Tensile Strength	425 * 325 W F	ASTM D-5034-95

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabrication and applying removable/reusable insulation or like products. All liabilities are borne by the user of this fabric. LEWCO does not take any responsibility for misuse of this product. LEWCO recommends testing before use.

S1650T-10152015MH