



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO 1750 SA-2 Silicone Impregnated Fiberglass Fabric

Product Specifications

LEWCO Style 1750 SA-2 is an asbestos free woven fiberglass fabric impregnated with a special chemical, water and oil resistant silicone rubber. LEWCO Style 1750 SA-2 is a flexible, light to medium weight fabric for removable insulation blankets.

This material is manufactured to conform to the following specifications:

- | | |
|--|--------------------|
| 1) NRC 1.36 | 3) ASTM E84 |
| 2) UL 723 Flame out spread 0, smoke development index 15 | 4) NFPA 255 |

Typical Properties

		<u>Test Method</u>
E-Glass Melting Point	1523 ° F	
Silicone Maximum Temperature	500 ° F	
Minimum Temperature	-80 ° F	
Type Weave	4 Harness Satin	
Color	Silver	
Type Fiberglass	E Glass	
Weight	17.5 Oz./Sq.Yd.	ASTM D-3776-96
Thickness	.0175 Inches	ASTM D-1777-96
Width	60 Inches	
Tensile Strength	500 * 400 W F	ASTM D-5034-95

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabrication and applying removable/reusable insulation or like products. All liabilities are borne by the user of this fabric. LEWCO does not take any responsibility for misuse of this product. LEWCO recommends testing before use.

S1750SA2-10152015MH