



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO Treated Fiberglass Fabric

Product Specifications

LEWCO Styles 1800 Z, 2100 Z, and 2800 Z are asbestos free and have been specially manufactured and coated with vermiculite to provide a higher temperature resistance in certain applications. This fabric works very well in welding curtain type applications. If this fabric is used for removable insulation jacketing against hot surfaces above 500°F, stainless steel blanket mesh is recommended due to considerable loss in tensile strength. Contact your LEWCO representative with your application.

Typical Properties

| | <u>1800 Z</u> | <u>2100 Z</u> | <u>2800 Z</u> |
|--------------------------------|---------------|---------------|---------------|
| Color | Gold | Gold | Gold |
| Weight (Oz./Sq.Yd.) | 19.0 | 21.0 | 28.0 |
| Thickness | .029" | .030" | .060" |
| Weave | Plain | Plain | Plain |
| Maximum Intermittent | 1500 ° F | 1500 ° F | 1500 ° F |
| Maximum Continuous Temperature | 1100 ° F | 1100 ° F | 1100 ° F |
| Width | 60" | 60" | 60" |

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabrication and applying removable/reusable insulation or like products. All liabilities are borne by the user of this fabric. LEWCO does not take any responsibility for misuse of this product. LEWCO recommends testing before use.

S2100Z-10152015MH