



6859 Renoir Avenue  
Baton Rouge, LA 70806

Tel: (225) 924-3221  
Fax: (225) 927-2918

## LEWCO 3000 SA-2 Silicone Impregnated Fiberglass Fabric

---

### Product Specifications

LEWCO Style 3000SA-2 is an asbestos free woven fiberglass fabric impregnated with a special chemical, water and oil resistant silicone rubber. LEWCO Style 3000SA-2 is a flexible heavy weight fabric for removable insulation blankets and welding curtains.

---

### Typical Properties

		<u>Test Method</u>
E Glass Melting Point	1523 ° F	
E-Glass Max Operating Temperature	1000 ° F	
Maximum Temperature	500 ° F	
Minimum Temperature	-80 ° F	
Color	Aluminized Pigment	
Type Fiberglass	E Glass	
Type Weave	8 Harness Satin	
Weight (Total)	32-34 Oz./Sq.Yd.	ASTM D-3776-96
Thickness	.032 Inches	ASTM D-1777-96
Width	60 Inches	
Tensile Strength	950 * 800 W F	ASTM D-5034-95

---

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabricating and applying removable insulation or like products. LEWCO does not take any responsibility for misuse of this product. All liabilities are borne by the user. LEWCO recommends testing before use.

S3000SA2-10152015MH