



Specialty Products, Inc.

6859 Rencir Avenue
Baton Rouge, LA 70806
(225) 924-3221
FAX (225) 927-2918

Toll Free (800) 221-6414
AR, TX (800) 233-9755
Email: Lewco@LewcoSpecialtyProducts.com
www.LewcoSpecialtyProducts.com

LEWCO KSS10-1L

Kevlar/10 Strand Stainless Steel Sewing Thread, Lubed

Our KSS10-1L sewing thread is made w/ 10 strands of 0.002", 304SS wire with a Kevlar core and wrap to give this thread strength and durability during the sewing operation. This thread is lubricated with silicone for ease of sew.

Technical Data Sheet

Product	Kevlar/10 Strand Stainless Steel
Yarn:	Filament Kevlar/.002 Type 304 SS
Diameter	.012
Average Yield	2,056 yards or 6,168 ft./lb
Average Break Load	23 Lbs.
Color	Natural Yellow
Elongation	3%
Packaging	Approx. 2.5 Lbs. per Spool
Maximum Continuous Temperature	1000°F
Suggested Max Use Temperature	1500° F
Melting Point – Stainless Steel	2732° F (1500° C)

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabricating removable/reusable insulation. LEWCO does not take any responsibility for misuse of this product. LEWCO strongly recommends testing prior to use.

SKSS10L-020711JDG