



6859 Renoir Avenue
Baton Rouge, LA 70806

Tel: (225) 924-3221
Fax: (225) 927-2918

LEWCO Fiberglass Ropes

Product Specifications

LEWCO Twisted, Braided and Square Braided Ropes are made from asbestos free, highly texturized silica based yarn.

Typical Properties

<u>Twisted</u>			<u>Braided</u>			<u>Sq. Braided</u>		
Diameter – Ft./ Spool			Diameter – Ft./Spool			Diameter – Ft./Spool		
1/4 “	-	1080	1/4 “	-	824	1/4 “	-	620
3/8 “	-	532	3/8 “	-	384	3/8 “	-	312
1/2 “	-	346	1/2 “	-	225	1/2 “	-	171
5/8 “	-	207	5/8 “	-	150	5/8 “	-	112
3/4 “	-	155	3/4 “	-	122	3/4 “	-	75
7/8 “	-	144	7/8 “	-	83	7/8 “	-	59
1 “	-	86	1 “	-	71	1”	-	46
			1 1/4 “	-	47			
			1 1/2”	-	33	1 1/2 “	-	21
			2 “	-	18			
			3 “	-	9			

Continuous Temperature Resistance 1100 ° F
Standard Spool Size is 25 lbs; Length can vary up to ±5%.
5 lb. spools available upon request
This is also available in 100’ lengths.

This information is given in good faith and is believed to be accurate. All liabilities are borne by the user. LEWCO does not take any responsibility for misuse of these products. LEWCO recommends testing before use. SFGROPES-102715MH