



Specialty Products, Inc.

6859 Renoir Avenue
Baton Rouge, LA 70806
(225) 924-3221
FAX (225) 927-2918

Toll Free (800) 221-6414
AR, TX (800) 233-9755
Email: Lewco@LewcoSpecialtyProducts.com
www.LewcoSpecialtyProducts.com

LEWCO SS/RG Fabric

High Temperature 304SS/Ceramic Fiber Fabric

Product Specifications

LEWCO Style SS/RG Fabrics are made of 2300°F Ceramic Fiber, 304 Stainless Steel 0.006" wire inserted yarn. The intended use for these products is in all high temperature applications where the need for thermal insulation and/or protection is required. Offers excellent protection against heavy sparks, spatters, and molten slag. LEWCO Style SS/RG Fabrics are also ideal very high temperature blanket applications such as engine exhaust systems with and without turbo chargers.

Typical Properties

	<u>SS/RGF-2</u>	<u>SS/RGF-6</u>	<u>SS/RGF-9</u>
Color	White	White	White
Thickness	.079"	.23"	.354"
Weave	Plain	Multi-Layer	Multi-Layer
Steady Use Temperature	2300 ° F	2300 ° F	2300 ° F
Melt Point	3000 ° F	3000 ° F	3000 ° F
Width	40"	40"	40"
Approximate Roll Length	32.8 Yards	10.9 Yards	10.9 Yards

This information is given in good faith and is believed to be accurate. It is intended for use by persons skilled in the art of fabrication and applying removable/reusable insulation or like products, as well as those working with welding curtains and fire blankets. All liabilities are borne by the user of this fabric. LEWCO does not take any responsibility for misuse of this product. LEWCO recommends testing before use.
SLEWCOSILSSRGF-06/27/07JBD